



# Skim Coat Excel

**EUROTILES SKIMCOAT EXCEL 102** is a ready-to-use smooth rendering paste that can be applied on both interior and exterior walls and ceilings in a thickness 0.3 to 4mm used to level surface defects in concrete or render.

## USES

- Lightweight concrete blocks
- Shuttered concrete
- Reinforced concrete
- Precast concrete
- Concrete soffits
- Fiber cement board

### *Possible covering materials:*

- thick plastic coating
- paint
- wallpaper
- fabric
- bonded plastic coverings

## ADVANTAGES

- Ready to use
- Easy to apply
- Superb smooth white finish
- Can be used in interior and exterior application
- Can be painted directly, no primer needed

## TECHNICAL DATA

	Days	mpa	psi
<b>Bond strength by Pull-off Test</b>	7	1.20	174
ASTM C1583 After 2 coats	28	1.50	217

<b>Coverage</b>	:	0.7 to 0.9kg / m <sup>2</sup> / 2 coats
<b>Packaging</b>	:	20kg pail
<b>Storage</b>	:	Cool, dry place
<b>Shelf life</b>	:	12 months (unopened container)

## HOW TO USE

### A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other particles and without any trace of oil, grease, laitance, paint or curing compound.
- Excess concrete and seas must be struck off.
- Using a sponge or a cloth, dampen the substrate before applying Eurotiles Skimcoat Excel 102.

### B. Application

- Apply small quantities of Eurotiles Skimcoat Excel 102 using a stainless steel trowel, filling knife or spatula.
- Regularly wash tools to remove hardened residues. DO NOT return or mix the residues into the bucket.
- Minimum of two coats must be applied for a successful resurfacing. First coat acts as primer to fill up all minor defects on the surface. Two or more coats can be applied depending on desired smoothness of the surface.
- Depending on the atmospheric condition, thickness application and covering materials, allow 15-30 minutes between each coat if Eurotiles Skimcoat Excel 102.
- Pre-covering curing time is 48-72 hours depending on the application thickness, atmospheric condition and covering materials.

## ***PRECAUTIONS***

- Do not apply to a wet or damp surface with moisture content.
- Do not apply the product more than 1mm per coat.
- Do not cover with hydraulic binder based mortar.
- Do not return the residues back to the bucket or pail of fresh, unused Eurotiles Skimcoat Excel 102.

**DISCLAIMER:** Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

**PRODUCT MADE IN THE PHILIPPINES**

## **EUROTILES INDUSTRIAL CORPORATION**

Unit 201 Prestige Tower, F. Ortigas Jr. Rd., Ortigas Center, Pasig City  
Tel. No.: (632) 635-2310 to 16  
[www.eurotilesconstructionchemicals.com](http://www.eurotilesconstructionchemicals.com)