



# Skim Coat Excel

*Eurotiles SkimCoat Excel* is a ready-to-use smooth skim rendering paste for thickness 0.3-4mm used to level surface defects in concrete or render.

## USES

*Eurotiles SkimCoat Excel* can be applied on both interior and exterior walls and ceilings in a thickness of 0.3 to 4mm.

*It can be applied on:*

- Lightweight concrete blocks
- Shuttered concrete
- Reinforced concrete
- Precast concrete
- Concrete soffits
- Fiber cement board

*Possible covering materials:*

- thick plastic coating
- paint
- wallpaper
- fabric
- bonded plastic coverings

## ADVANTAGES

- Ready to use
- Easy to apply
- Superb smooth white finish
- Can be used in interior and exterior application
- Can be painted directly, no primer needed

## TECHNICAL DATA

	Days	MPa	PSI
Bond Strength by Pull-Off Test ASTM C1583 After 2 Coats	7	1.20	174
	28	1.50	217

**Coverage area:** 0.7-0.9 kg/m<sup>2</sup>/2 coats (depending on the quality of the substrate)

**Packaging:** 20 kg pail

**Storage:** store in a cool, dry place

**Shelf life:** 12 months (unopened container)

## **HOW TO USE**

1. The substrate must be clean and sound, free from dust and other particles, without any trace of oil or grease, laitance, paint or curing compound.
2. Excess concrete and seams must be struck off.
3. Using a sponge or cloth, damp the substrate before application of Eurotiles SkimCoat Excel.

### **B. Application**

1. Apply small quantities of Eurotiles SkimCoat Excel using a stainless steel trowel, filling knife or spatula.
2. Regularly wash tools to remove hardened residues, DO NOT return or mix the residues into the bucket.
3. Minimum of two coats must be applied for a successful resurfacing. First coat acts as primer to fill up all minor defects on the surface. Two or more coats can be applied depending on desired smoothness of the surface.
4. Depending on the atmospheric condition, thickness application and covering materials, allow 15-30 minutes between each coat of Eurotiles SkimCoat Excel.
5. Pre-covering curing time is 48-72 hours depending on the application thickness, atmospheric condition and covering materials.

## **PRECAUTIONS**

- Do not apply to a wet or damp surface with high moisture content.
- Do not apply the product more than 1mm per coat.
- Do not cover with hydraulic binder-based mortar.
- Do not return the residues back to the bucket/pail of fresh, unused Eurotiles SkimCoat Excel.

Disclaimer: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

MADE IN TAIWAN

### **EUROTILES INDUSTRIAL CORPORATION**

Unit 201, Prestige Tower, F. Ortigas Jr. Road, Ortigas Center, Pasig City

Tel. No.: (632) 635-2310 to 16 Fax No. (632) 635-2317

[www.eurotiles.ph](http://www.eurotiles.ph)