



EUROTILES PRIMER KOTE 216 is a bonding primer that creates a bonding key on smooth and sealed substrates or porous substrates. It improves the condition of the substrate, the bonding strength of the mortar and minimizes pinholes. It also improves the absorption capacity of the substrate.

USES

- Reinforced concrete,
- Precast concrete panels
- Traditional renderings

TECHNICAL DATA

Ratio	1 part Eurotiles Primer Kote 216 : 2 parts water
Dry Time	1 – 2 hours
Coverage	0.16 kg/mm ²
Packaging	20 liter pail
Storage	cool, dry place
Shelf life	12 months (unopened container)

HOW TO USE

A. Substrate Preparation

- The substrate must be compliant with the building regulations and it must be cured for at least 28 days.
- The substrate must be clean and sound, solid, free from dust and without any trace of oil grease, laitance, curing compound, plaster or paints and any other products that may effect affect bonding.
- The substrate must be stripped of any excessive trace of wax, paint or grease.
- All substrates must be soaked in water until no bubbles are present.
- When bubbles are no longer visible, remove the excess water. The substrate must be damp prior to the application.

B. Application

- Mix Eurotiles Primer Kote 216 properly before applying.
- Apply Eurotiles Primer Kote 216 by brush or roller
- Allow 1-2 hours drying time depending on the substrate, temperature and relative humidity.
- The primer must be covered within 24 hours

PRECAUTIONS

- Temperature range - 5°C- 35°C
- Clean tools immediately after use.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN TAIWAN

EUROTILES INDUSTRIAL CORPORATION

Unit 201 Prestige Tower, F. Ortigas Jr. Rd., Ortigas Center, Pasig City
Tel. No.: (632) 635-2310 to 16
www.eurotilesconstructionchemicals.com