EUROTILES

Skim Coat Eco

EUROTILES SKIMCOAT ECO 100 is a smooth rendering liquid to be mixed with cement at thickness of 0.3 to 4mm for use to eliminate grooves, seams and rock pockets in concrete surface for a seamless smooth finish.

USES

- Interior and exterior walls and ceilings from 0.4 to 4mm thickness
- Reinforced concrete
- Pre-cast concrete panels
- Traditional rendering mortars
- Lightweight concrete or lightweight block
- Fiber cement board

ADVANTAGES

- Seamlessly smooth finish
- High bonding strength
- Can be painted directly, no primer needed

TECHNICAL DATA

	Days	mpa	psi
Bond strength by Pull-off Test ASTM C1583 1mm thickness	7	1.23	178
	28	1.31	190
Compressive Strength ASTM C109	7	11	1595
	28	20	2900

Coverage	:	0.6 to 0.8 kg / m^2 / 2 coats
Packaging	:	20kg pail
Storage	:	Cool, dry place
Shelf life	:	12 months (unopened container)

HOW TO USE

A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other particles and without any trace of oil, grease, laitance, paint or curing compound.
- Excess concrete and seas must be struck off.
- Using a sponge or a cloth, dampen the substrate before applying Eurotiles Skimcoat Eco 100.

B. Product Preparation

- Mix 1 part of Euoritles Skimcoat Eco 100 with 1 part cement (1:1) unitl a homogeneous, lump free consistency is achieved. **Do not add water.**

C. Application

- Using a stainless steel filling knife or trowel, apply Eurotiles Skimcoat Eco 100 onto the substrate.
- Apply a minimum of two coats.
- Depending on the thickness and the atmospheric condition, allow 15-30 minutes between each coat of Eurotiles Skimcoat Eco 100.
- Allow a minimum of 7 days for curing depending on the thickness of the coat and the atmospheric conditions.

PRECAUTIONS

- Temperature range: 5°C to 35°C
- Immediately clean tools after application with water before product dries,
- Protect the finished surface from drying out by lightly moistening during hot conditions.
- Do not cover with hydraulic binder based mortar.
- Do not immerse the product.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Unit 201 Prestige Tower, F. Ortigas Jr. Rd., Ortigas Center, Pasig City
Tel. No.: (632) 635-2310 to 16
wwww.eurotilesconstructionchemicals.com